

Infotrend EonStor DS Expansion Enclosures



Through SAS expansion ports, each EonStor DS storage system can connect with robust and high-density expansion enclosures to provide a maximum capacity of 144 SAS drives. The incremental approach of capacity scaling effectively satisfies growing application needs while reducing wasted upfront investment.

| Technical Specifications | | 2.5-inch SAS Drives | | | |
|--|--|---|--|------------------------------------|--|
| | ESDS B12S-J2000-R | ESDS B12S-J2000-G | ESDS B12S-J1000-R | ESDS B12S-J1000-S | |
| Controller | Dual redundant | Single | Dual redundant | Single | |
| Host Connectivity | Two (2) 6Gb/s SAS 4x wide ports per controller | | Two (2) 3Gb/s SAS 4x wide ports per controller | | |
| Drive Connectivity | Exclusively 6Gb/s SAS | | Exclusively 3Gb/s SAS | | |
| Drive Bays | 12 | | | | |
| Corresponding EonStor DS Models¹ | ESDS B12F-R2840 ESDS B12S-R2240 ESDS B12E-R2140 | ESDS B12F-G2840 ESDS B12S-G2240 ESDS B12E-G2140 | ESDS B12F-R1430 ESDS B12S-R1030 | ESDS B12F-G1431 ESDS B12S-G1031 | |
| Power Supplies | Two redundant 380W | Two redundant 250W | Two redundant 380W | Two redundant 380W | |
| Form Factor² | 1U, 19-inch rackmount | | | | |
| Service and Support³ | | | | | |
| Standard Service | 3-year limited hardware warranty and 8x5 phone, web and email support | | | | |
| Upgrade/Extension Options | Replacement part dispatch on the next business day (up to 5 years) Advanced Service: 24x7 phone, web and email support + onsite diagnostics on the next business day (up to 5 years) Premium Service: 24x7 phone, web and email support + onsite diagnostics in 4 hours (up to 5 years) Extended Standard Service up to 5 years | | | | |

| Technical Specifications | | 2.5-inch SAS Drives | |
|--|--|--|--|
| | ESDS B24S-J2000-R | ESDS B24S-J2000-S | |
| Controller | Dual redundant | Single | |
| Host Connectivity | Two (2) 6Gb/s SAS 4x wide ports per controller | | |
| Drive Connectivity | Exclusively 6Gb/s SAS | | |
| Drive Bays | 24 | | |
| Corresponding EonStor DS Models¹ | ESDS B24F-R2842 ESDS B24F-R2840 ESDS B24S-R2240 ESDS B24E-R2142 | ESDS B24F-G2842 ESDS B24F-G2840 ESDS B24S-G2240 ESDS B24E-G2142 | |
| Power Supplies | Two redundant 530W | | |
| Form Factor² | 2U, 19-inch rackmount | | |
| Service and Support³ | | | |
| Standard Service | 3-year limited hardware warranty and 8x5 phone, web and email support | | |
| Upgrade/Extension Options | Replacement part dispatch on the next business day (up to 5 years) Advanced Service: 24x7 phone, web and email support + onsite diagnostics on the next business day (up to 5 years) Premium Service: 24x7 phone, web and email support + onsite diagnostics in 4 hours (up to 5 years) Extended Standard Service up to 5 years | | |

1. Please refer to corresponding models for the supported drives of expansion enclosures.

2. For detailed dimensions, please visit the Infotrend website.

3. All EonStor DS systems are shipped with Standard Service.

| | ESDS S16S-J2000-R | ESDS S16S-J2000-S | ESDS S12S-J2000-R | ESDS S12S-J2000-G |
|--|---|--|--|--|
| Controller | Dual redundant | Single | Dual redundant | Single |
| Host Connectivity | Two (2) 6Gb/s SAS 4x wide ports per controller | | | |
| Drive Connectivity | Exclusively 6Gb/s SAS | | | |
| Drive Bays | 16 | 16 | 12 | 12 |
| Corresponding EonStor DS Models¹ | ESDS S24F-R2840 ESDS S16F-R2842 ESDS S16F-R2840 ESDS S16S-R2240 ESDS S16E-R2240 ESDS S16E-R2142 ESDS B24F-R2842 ESDS B24F-R2840 ESDS B24S-R2240 ESDS B24E-R2142 ESDS B12F-R2840 ESDS B12S-R2240 ESDS B12E-R2140 | ESDS S24F-G2840 ESDS S24S-G2240 ESDS S24E-G2142 ESDS S16F-G2842 ESDS S16F-G2840 ESDS S16S-G2240 ESDS S16E-G2240 ESDS S16E-G2142 ESDS B24F-G2842 ESDS B24F-G2840 ESDS B24S-G2240 ESDS B24E-G2142 ESDS B24S-G2240 ESDS B12F-G2840 ESDS B12S-G2240 ESDS B12E-G2140 | ESDS S12F-R2840 ESDS S12S-R2240 ESDS S12E-R2140 ESDS B24F-R2842 ESDS B24F-R2840 ESDS B24S-R2240 ESDS B24E-R2142 ESDS B12F-R2840 ESDS B12S-R2240 ESDS B12E-R2140 | ESDS S12F-G2840 ESDS S12S-G2240 ESDS S12E-G2140 ESDS B24F-G2842 ESDS B24F-G2840 ESDS B24S-G2240 ESDS B24E-G2142 ESDS B12F-G2840 ESDS B12S-G2240 ESDS B12E-G2140 |
| Power Supplies | Two redundant 530W | Two redundant 530W | Two redundant 530W | Two redundant 350W |
| Form Factor² | 3U, 19-inch rackmount | 3U, 19-inch rackmount | 2U, 19-inch rackmount | 2U, 19-inch rackmount |

Technical Specifications

3.5-inch 3Gb/s SAS Drives

| | ESDS S16S-J1000-R | ESDS S16S-J1000-S | ESDS S12S-J1002-R | ESDS S12S-J1000-G |
|--|--|--|--|---|
| Controller | Dual redundant | Single | Dual redundant | Single |
| Host Connectivity | Two (2) 3Gb/s SAS 4x wide ports per system | | | |
| Drive Connectivity | Exclusively 3Gb/s SAS | | | |
| Drive Bays | 16 | 16 | 12 | 12 |
| Corresponding EonStor DS Models¹ | ESDS S24F-R1840 ESDS S24F-R1440 ESDS S16F-R1840 ESDS S16F-R1440 ESDS S16S-R1030 ESDS S16E-R1130 ESDS B12F-R1430 ESDS B12S-R1030 | ESDS A24S-G2130 ESDS S16S-G1030 ESDS S16F-G1840 ESDS S16F-G1440 ESDS S16E-G1140 ESDS S16E-G1130 ESDS B12F-G1431 ESDS B12S-G1031 | ESDS S12F-R1840 ESDS S12F-R1440 ESDS S12S-R1032 ESDS S12E-R1132 ESDS B12F-R1430 ESDS B12S-R1030 | ESDS S12F-G1842 ESDS S12F-G1440 ESDS S12F-G1433 ESDS S12S-G1033 ESDS S12E-G1140 ESDS B12F-G1431 ESDS B12S-G1031 |
| Power Supplies | Two redundant 530W | Two redundant 530W | Two redundant 530W | Two redundant 460W |
| Form Factor² | 3U, 19-inch rackmount | | 2U, 19-inch rackmount | |
| Service and Support³ | | | | |
| Standard Service | 3-year limited hardware warranty and 8x5 phone, web and email support | | | |
| Upgrade/Extension Options | Replacement part dispatch on the next business day (up to 5 years) Advanced Service: 24x7 phone, web and email support + onsite diagnostics on the next business day (up to 5 years) Premium Service: 24x7 phone, web and email support + onsite diagnostics in 4 hours (up to 5 years) Extended Standard Service up to 5 years | | | |

1. Please refer to corresponding models for the supported drives of expansion enclosures.
2. For detailed dimensions, please visit the Infotrend website.
3. All EonStor DS systems are shipped with Standard Service.

© 2011 Infotrend Technology, Inc. All rights reserved.
 - Any information provided herein is without warranties of any kind of and is subject to change without prior notice.
 - Infotrend, SANWatch, EonPath and ESVA are registered trademarks of Infotrend Technology, Inc.
 - Infotrend logo is a trademark of Infotrend Technology, Inc.
 - All other names, brands, or services are trademarks or registered trademarks of their respective owners.



Asia Pacific
 Infotrend Technology, Inc.
 Tel:+886-2-2226-0126
 E-mail : sales.ap@infotrend.com
 Technical Support :
<http://esupport.infotrend.com.tw>
 Website:
<http://www.infotrend.com>

Americas
 Infotrend Corporation
 Tel:+1-408-988-5088
 E-mail : sales.us@infotrend.com
 Technical Support :
<http://esupport.infotrend.com>
 Website:
<http://www.infotrend.com/americas>

Europe (EMEA)
 Infotrend Europe Ltd.
 Tel:+44-1256-707-700
 E-mail : sales.eu@infotrend.com
 Technical Support :
<http://esupport.infotrend-europe.com>
 Website:
<http://www.infotrend.com/europe>

Germany
 Infotrend Deutschland GmbH
 +49-(0)89-207042650
 E-mail : sales.de@infotrend.com
 Technical Support :
<http://esupport.infotrend-europe.com>
 Website:
<http://www.infotrend.com/germany>

China
 Infotrend Technology, Ltd.
 Tel:+86-10-63106168
 E-mail : sales.cn@infotrend.com
 Technical Support :
<http://esupport.infotrend.com.cn>
 Website:
<http://www.infotrend.com/china>

Japan
 Infotrend Japan, Inc.
 Tel:+81-3-5730-6551
 E-mail : sales.jp@infotrend.com
 Technical Support :
<http://esupport.infotrend.com.tw>
 Website:
<http://www.infotrend.com/japan>