



EonStor GS U.2 NVMe All-Flash Storage

Scale-out Unified Storage with High Availability for Enterprises

Highlights

Extreme Performance

- Up to 1100K IOPS to accelerate storage operations
- Massive sequential throughput of up to 24GB/s read and 12GB/s write

Cost-Effective Storage

- U.2 NVMe SSD to deliver better performance at lower costs
- Automated storage tiering to fully utilize SSD and HDD

Flexible Scalability

- Scale-out and scale-up expansions to easily expand performance and capacity to more than 40PB

Easy to Use and Manage

- Single namespace for easier data access
- Auto-balancing to reduce the burden of storage management for IT staff

Nondisruptive Operations

- HA service ensures non-stop operations with a near-zero RTO (recovery time objective) by deploying two storage devices to provide services from two separate sites.

Introduction

EonStor GS U.2 NVMe all-flash storage is a high performance storage solution for enterprises. Equipped with U.2 NVMe SSD, it delivers higher IOPS and throughput at a cost-effective price. This unified storage series supports both SAN and NAS services, provides block-level and file-level scale-out expansions to linearly increase performance and capacity, and comes with complete data protection that allows IT staff to focus on higher value projects. It thus makes a perfect fit for applications such as HPC, M&E, virtualization, and database.

End-to-End High Performance with U.2 NVMe SSD

Supporting PCIe 4.0, NVMe U.2 SSD, and 100GbE connectivity with RDMA, GS U.2 NVMe storage delivers a higher speed with a lower latency, providing up to 24GB/s read and 12GB/s write in throughput and 1100K on a single appliance.

Cost-Effectiveness and High Storage Efficiency

U.2 NVMe SSD is becoming the mainstream in the market as it combines the advantages of SAS and SATA SSDs, allowing enterprises to enjoy higher performance at a competitive price.

EonStor GS U.2 NVMe storage supports hybrid storage, and with automated storage tiering, the storage system can automatically leverage the high throughput and low latency of U.2 NVMe SSDs for frequently accessed data, while using HDDs on expansion enclosures as data backup media, thereby boosting system performance at a reduced total cost of ownership.

EonStor GS U.2 NVMe storage also comes with inline compression and offline deduplication, which reduces the required storage capacity and thus saves storage costs. The inline compression feature compresses raw files in real-time, which greatly shrinks the data size and reduces the transfer time. To deal with repeated files saved by manual backups or archiving, offline deduplication helps you automatically remove duplicate data from the cluster to free up storage space.

Flexible Scalability with Scale-out and Scale-up

Through scale-out expansion, you can linearly increase performance and capacity for both block-level and file-level environments. When one storage appliance is no longer able to provide enough performance or capacity, you can simply add more appliances to form a cluster—with a maximum of 4 appliances.

Through scale-up expansion, each storage appliance can be connected to JBOD expansion enclosures to add up to 896 drives. Together with scale-out expansion, EonStor GS U.2 NVMe storage supports more than 3000 drives in total.

Easy Data Access for Users and Simple IT Management

Users can access shared folders in a single root directory under a single namespace, without having to worry about where the data is stored. Auto-balancing is also supported to achieve load balancing, which relieves the burden of manual planning and configuration for IT personnel.

Smart Management of SSD

EonStor GS U.2 NVMe storage uses an intelligent algorithm to handle data writes and optimize SSD usage. The algorithm not only extends SSD lifespan by reducing the total amount of writes on an SSD but also prevents multiple SSDs from failing at the time and causing data loss. Moreover, as EonStor GS U.2 NVMe storage monitors SSD status in real time, it estimates the remaining lifespan of each SSD and sends the administrator a reminder to replace the SSD that is about to fail.

Complete Data Protection and Backup

EonStor GS U.2 NVMe offers various data protection mechanisms to guarantee data safety. First, Infortrend's unique RAID technology ensures your data remains intact even in case of a drive failure. With snapshot, a flexible backup tool, you can back up local resources on a storage system by schedule, including volumes and shared folders, and roll back to a previous version when needed. For further protection, you can back up data to a remote GS appliance using the remote replication feature, or to a public cloud with EonCloud Gateway.

Immutable object storage, another crucial feature for data protection, safeguards data against ransomware attacks. It retains data with WORM (write once read many) storage protection, where data gets “locked” and therefore cannot be modified, deleted, overwritten, or even encrypted by ransomware. By setting a retention period, you can easily follow government compliance requirements or company policies on data retention.

New Level of High Availability

From power supplies, cooling fans, controllers, to host boards, the modular design of all these hardware components lowers maintenance complexity and provides fast, precise technical support and RMA services, keeping EonStor GS U.2 NVMe storage safe from any downtime to maintain nonstop services, increase productivity, and enhance competitiveness.

In addition, EonStor GS U.2 NVMe storage offers HA service to deliver continuous availability with a near-zero RTO (recovery time objective) and a zero RPO (recovery point objective). With two storage devices deployed at near sites, the HA service provides block-level active-active storage and file-level active-passive storage for business-critical applications that have an extremely low tolerance for downtime. Featuring synchronous remote replication and auto-failover, this solution ensures identical and complete copies of data are stored on both storage devices and avoids service downtime due to planned or unexpected events. Auto-failback is available in block-level HA service, allowing a storage device to resume services without manual intervention.

Intuitive Management Software

GS U.2 NVMe storage adopts EonOne, a web-based management software tool, to assist customers in raising storage and service efficiency for increased productivity. With its intuitive interface design, IT administrators can easily manage a cluster and multiple appliances, monitor performance and capacity usage, and complete system configurations, all from one centralized interface.

PHYSICAL SPECIFICATIONS

Product Series		GS 2000U	GS 3000U	GS 3000UT	GS 4000U
Form Factor	2U 24-bay	GS 2024UR	GS 3024UR	GS 3024URT	GS 4024UR
Note: U: NVMe storage, R: Dual redundant controllers, T: High performance					
Controller	Dual redundant				
Cache Backup Technology	Super capacitor + flash module				
CPU	Intel® Xeon® D 2-Core	Intel® Xeon® D 4-Core	Intel® Xeon® D 4-Core	Intel® Xeon® D 6-Core	Intel® Xeon® D 6-Core
Cache Memory	Default DDR4 16GB Expandable up to 128GB	Default DDR4 16GB Expandable up to 128GB	Default DDR4 48GB Expandable up to 384GB	Default DDR4 48GB Expandable up to 384GB	Default DDR4 48GB Expandable up to 384GB
Supported Drives	2.5" U.2 NVMe SSD (must be purchased from Infortrend)				
Note: For the latest compatibility details, refer to our official website for the latest Compatibility Matrix.					
Max. Drive Number	via expansion enclosure, per appliance	896	896	896	896
	via scale-out with other series of appliances, per cluster	3584	3584	3584	3584
Max. SSD Cache Pool (Block-level)	4TB				
Onboard 10GbE Ports (SFP+)	0				
Onboard 25GbE Ports (SFP28)	0				
Max. Host Board Slots	4				
Host Board Options	16Gb/s FC x 4 32Gb/s FC x 2 32Gb/s FC x 4 10GbE (SFP+) x 2 25GbE (SFP28) x 2 12Gb/s SAS x 2			16Gb/s FC x 4 32Gb/s FC x 2 32Gb/s FC x 4 10GbE (SFP+) x 2 25GbE (SFP28) x 2 100GbE (QSFP28) x 1, RDMA 100GbE (QSFP28) x 2, RDMA 12Gb/s SAS x 2	
	Note: 1. One 100GbE x 2 host board delivers a maximum throughput of 100Gb/s. 2. For complete information, refer to our official website for the latest Host Board and Memory Guide.				
Max. 16Gb/s FC Ports	16				
Max. 32Gb/s FC Ports	16				
Max. 10GbE Ports (SFP+)	8				
Max. 25GbE Ports (SFP28)	8				
Max. 100GbE Ports (QSFP28)	0				
Max. 12Gb/s SAS Ports	8				
Expansion Enclosures (JBODs)	JB 3012A, JB 3016A, JB 3024BA, JB 3025BA, JB 3060L				
Dimensions (Without Chassis Ears and Protrusions) (W x H x D)	449 x 88 x 500 mm			449 x 88 x 530 mm	
Package Dimensions (W x H x D)	780 x 338 x 588 mm				
Power Supply Unit	Power Supplies (Redundant and Hot-swappable)	530W x 2 (80 PLUS Bronze)			
	AC Voltage	100VAC @10A to 240VAC @5A			
	Frequency	50-60 Hz			
Safety Standards	<ul style="list-style-type: none"> Electromagnetic Compatibility : CE, BSMI, FCC Safety : UL, BSMI, CB 				

SOFTWARE SPECIFICATIONS

Max. Logical Drive Number	30	
Max. Logical Drive Capacity	512TB	
Stripe Size	16KB, 32KB, 64KB, 128KB, 256KB, 512KB, or 1024KB per logical drive	
Write Policy	Write-Back or write-through per logical drive.	
Max. Pool Size	2PB	
Max. Pool Number	30	
Max. Volume Size	2PB	
Max. Volume Number	1024	
Max. Host LUN Mapping Number	4096	
Max. Reserved Tag Number (per Host-LUN Connection)	256	
Max. iSCSI Initiators	832	
Max. Host Connection Number (per FC)	128	
RAID Options	RAID 0, RAID 1, RAID 3, RAID 5, RAID 6, RAID 10, RAID 30, RAID 50, RAID 60	
Supported Protocols	File Level	CIFS/SMB (Version 2.0/3.0), NFS (Version 2/3/4), AFP (Version 3.1.12), FTP/FXP (vsftp 2.3.4), WebDAV (httpd package 2.4.6)
	Block Level	FC, iSCSI, SAS
	Object Level	RESTful API
File Level	Max. File System Size	2PB
	Max. Number of User Accounts	20000
	Max. Number of User Groups	512
	Max. Number of Shared Folder	2048 (NFS/CIFS/FTP) 255 (AFP)
	Max. Number of Rsync Jobs	1024
	Max. Number of Concurrent Rsync Processes	64
	Max. Number of Connections	2048 (NFS/CIFS/AFP) 1024 (FTP)
Management	<ul style="list-style-type: none"> • SMI-S standard interface for hypervisor management applications • Multi-factor authentication login mechanism • Web-based EonOne management software • User account management • Group management 	<ul style="list-style-type: none"> • Folder management - folder access control • Quota management • Folder encryption with AES • Integration with Microsoft Active Directory (AD) and Linux LDAP • Storage Resource Management to analyze history of resource usage
Availability and Reliability	<ul style="list-style-type: none"> • Immutable object storage • Hot-swappable hardware modules • Device mapper • Antivirus • Trunk group 	<ul style="list-style-type: none"> • Cache safe technology • UPS • WORM (file level only) • SMB Multichannel
Efficiency	<ul style="list-style-type: none"> • Inline compression • Offline deduplication 	
Notification	<ul style="list-style-type: none"> • Email • SNMP traps 	
Applications	<ul style="list-style-type: none"> • Web-based file explorer • Proxy server • Syslog server • VPN server • LDAP server • Docker 	
Supported Cloud Services	<p>EonCloud Gateway supports integration with the following cloud providers: Amazon S3, Microsoft Azure, Alibaba Cloud, OpenStack, Baidu Cloud, Google Cloud, Tencent Cloud, Wasabi Cloud, etc.</p> <p>Note: For complete information about cloud provides support, please refer to EonCloud Gateway webpage https://www.infortrend.com/global/solutions/eoncloud</p>	
Supported OS	<p>Microsoft Windows Server, Red Hat Enterprise Linux, Mac OS X, VMware.</p> <p>Note: For the latest compatibility details, refer to our official website for the latest Compatibility Matrix.</p>	

DATA SERVICES

Thin Provisioning	Block level	Default	"Just-in-time" capacity allocation optimizes storage utilization and eliminates allocated but unused storage space.	
File Snapshot		Optional	Snapshot images per folder: 1024	
Local Replication	Snapshot	Block level	Default	Snapshot images per source volume: 64 Snapshot images per pool: 128
			Optional	Snapshot images per source volume: 256 Snapshot images per pool: 4096
	Volume Copy/Mirror	Default	Replication pairs per source volume: 4 Replication pairs per system: 16	
		Optional	Replication pairs per source volume: 8 Replication pairs per system: 256	
Remote Replication	File level	Default	Rsync with 128-bit SSH encryption	
	Block level	Optional	Replication pairs per source volume: 8 Replication pairs per system: 64	Note: 1. The maximum number of replication pairs per source volume is 8, whether they are remote asynchronous pairs, remote synchronous pairs, or local volume pairs. 2. 16Gb FC x 4, 32Gb FC x 2, and 32Gb FC x 4 host boards do not support Remote Replication.
Automated Storage Tiering		Optional	Storage tiers per pool: 4	
Scale-out	File level	Default	Appliances per cluster: 1	
		Optional	Appliances per cluster: 4	
	Block level	Default	Appliances per cluster: 4	
HA Service	File level	Optional	Delivering continuous availability and eliminating downtime for mission-critical workloads that require non-stop operations	
	Block level		Note: HA Service is not available on GS 2000U.	
SSD Cache	File level	Optional	Accelerating file operations and data access performance for both read and write Max. SSD number per controller: 8	
	Block level	Optional	Accelerating data access for random read-intensive environments (e.g. OLTP) Max. SSD number per controller: 4	
			Recommended DIMM capacity per controller for SSD Cache pool	
			DRAM:8GB	Max SSD Cache Pool Size: 0.5TB
			DRAM:16GB	Max SSD Cache Pool Size: 1TB
			DRAM:32GB	Max SSD Cache Pool Size: 2TB
DRAM:64GB and up	Max SSD Cache Pool Size: 4TB			

WARRANTY AND SERVICE

Service and Support	Standard Service	3-year limited hardware warranty and 8x5 phone, web, and email support (batteries are covered under warranty for 2 years)
	Upgrade or Extension Options	<p>Warranty extension: Standard service can be extended up to 5 years. The following service can be upgraded to 5 years.</p> <ul style="list-style-type: none"> • Upgrade: Replacement part dispatch on the next business day • Advanced service: 24x7 phone, web, and email support + onsite diagnostics on the next business day • Premium service: 24x7 phone, web, and email support + onsite diagnostics in 4 hours <p>Note: Options may vary by region. For more details, please contact our sales representatives.</p>
	Technical Support	Get information on system installation and maintenance, download technical documents and software, or issue a support ticket
	Product Services	Register products, download firmware, apply for licensing services, create product repair tickets, or check product repair status

Asia Pacific (Taipei, Taiwan)
Infotrend Technology, Inc.
Tel : +886-2-2226-0126
E-mail : sales.ap@infotrend.com

China (Beijing, China)
Infotrend Technology, Ltd.
Tel : +86-10-6310-6168
E-mail : sales.cn@infotrend.com

Japan (Tokyo, Japan)
Infotrend Japan, Inc.
Tel : +81-3-5730-6551
E-mail : sales.jp@infotrend.com

Americas (Sunnyvale, CA, USA)
Infotrend Corporation
Tel : +1-408-988-5088
E-mail : sales.us@infotrend.com

EMEA (Basingstoke, UK)
Infotrend Europe Ltd.
Tel : +44(0)-1256-305-220
E-mail : sales.eu@infotrend.com

