

Much more than just a bunch of drives

Convenient storage add-on

- Plug and play expansion -ideal for direct attached storage configurations
- Compatible with server-based host bus adapters and RAID cards
- Simpler than using a dedicated RAID system if all you need is storage

Great performance

- 12Gb/s SAS throughput ensures ample connection speed
- Enterprise-class reliable data transmission

Space for everyone

- 2U 12-bay to 4U 60-bay, pick the enclosure that is right for you
- High density with standard 19" rackmount form factor
- Up to 224 drives via host bus adapters or RAID cards

Highly available and green

- Dual redundant controllers provide offer a doubled data path to hard drives
- Up to three power supplies mean enclosures are very failure-resistant
- 80 PLUS units save energy to reduce environmental impact – and costs
- Smart cooling lowers noise and energy waste while boosting stability

Add convenient and easy to integrate storage to your servers with JB 300 rackmount enclosures. Working with a wide selection of Infortrend-qualified host bus adapters (HBA) and RAID cards, the user friendly 19" enclosures add high performance and high availability direct attached storage to your servers in true plug n play fashion. Available in multiple form factors and densities, JB 300 enclosures have been designed to provide quick and consistent access to big storage that is free from technical complexities.

Fast connectivity

JB 300 enclosures instantly add massive storage to go alongside servers and have the connection speed to keep up via reliable enterprise-class 12Gb/s SAS, which provides a combination of bandwidth and dependability

More room

Using a server equipped with a host bus adapter or RAID card, you can select a JB 300 enclosure with space for as many as 224 drives. Depending on model, JB 300 products work with 2.5" and 3.5" HDDs

High availability and hot pluggable design

We offer JB 300 enclosures with single and dual redundant controllers. The latter work with your HBA or RAID card to ensure high availability that protects data access, with a doubled data path to hard drives. All controllers are hot plug with simple installs, maintenance, and upgrades, making 300 enclosures easy to work with even if you are not an IT expert

Diverse form factors

From compact 2U 12-bay to large form factor and high density 60-bay models, JB 300 enclosures cater to a wide range of situations and demands. Whether an SMB or a large enterprise, they deliver the storage space you require while providing an equally flexible price spectrum

JB 300 series

Easy to work with

- Controllers and power supplies use a downtime-minimizing hot plug design
- Simple installs and maintenance plus ready for controller/PSU upgrades in future
- Hard drives organized into easy-reach drawers with vertical drive alignment for simple push and pull access (high density 60-bay models)

Smart and easy drawer layout

High density 60-bay JB 300 enclosures arrange drives into three drawers that can be easily opened and closed with one-hand convenience. Inside drawers, drives stand vertically and can be pushed in and pulled out with great ease – making for quick swaps if you need bigger drives, plus easy maintenance and replacement

JB 360



JB 360L



Eco-friendly and safe power delivery

JB 300 enclosures feature up to three redundant 80 PLUS power supplies rated for 530W/460W or 1600W/1200W each. These ensure highly efficient power delivery that saves you money on electric bills – a perfect match for non-stop server operation. Power supply fans deliver smart cooling based on system load, reducing energy waste and noise while ensuring optimized heat removal. On top of being very efficient, power supplies are carefully selected for endurance, and with solid redundancy your storage stays up and running even if one power supply requires maintenance





| Model | JB 324RB | JB 324SB | JB 312R | JB 312S |
|---|---|----------|-----------------------------|---------------|
| Form factor ² | 2U SFF 19-inch rackmount | | 2U LFF 19-inch rackmount | |
| Drive bay | 24 | | 12 | |
| Controller | Dual redundant | Single | Dual redundant | Single |
| Host/Expansion connectivity (per controller) | 2 x 12Gb/s Mini SAS HD ports (SFF-8644) | | | |
| Controller support | • LSI 12Gb/S SAS RAID card - MegaRAID SAS 9380-8e | | | |
| Supported drives ¹ | 2.5" 10000 RPM SAS 2.5" 15000 RPM SAS 3.5" 7200RPM SAS(JB312 only) | | | |
| Maximun drives (via expansion to additional enclosures) | 216 | | 180 | |
| Hot-swappable power supply | Two redundant 460W | | | |
| Green design | 80 PLUS power supplies delivering more than 80% energy efficiency | | | |
| Avaiability | Redundant, hot-swappable hardware modules | | | |
| Notification | LED status | | | |
| Service and Support | Standard service 3-year limited hardware/software warranty and 8x5 phone, web and email support | | | email support |
| | Replacement part dispatch on the next business day (up to 5 years) Advanced Service: 24x7 phone, web and email support + onsite diagnostics on the next business day (up to 5 years) Premium Service: 24x7 phone, web and email support + onsite diagnostics in 4 hours (up to 5 years) Extended Standard Service up to 5 years | | | |





| Model | JB 316F | JB 316S | |
|---|--|--|--|
| Form factor ² | 3U LFF 19-inch rackmount | | |
| Drive bay | 16 | | |
| Controller | Dual redunda | nt Single | |
| Host/Expansion connectivity (per controller) | 2 x 12Gb/s Mini SAS HD ports (SFF-8644) | | |
| Controller support | LSI 12Gb/S SAS RAID card MegaRAID SAS 9380-8e | | |
| Supported drives ¹ | 2.5" 15000 RPM SAS 2.5" 10000RPM SAS 3.5" 7200RPM SAS | | |
| Maximun drives (via expansion to additional enclosures) | 224 | | |
| Hot-swappable power supply | Two redundant 460W | | |
| Green design | 80 PLUS power supplies delivering more than 80% energy efficiency | | |
| Avaiability | Redundant, hot-swappable hardware modules | | |
| Notification | LED status | | |
| | Standard service | 3-year limited hardware/software warranty and 8x5 phone, web and email support | |
| Service and Support | Replacement part dispatch on the next business day (up to 5 years) Advanced Service: 24x7 phone, web and email support + onsite diagnostics on the next busines (up to 5 years) Premium Service: 24x7 phone, web and email support + onsite diagnostics in 4 hours (up to 5 years) Extended Standard Service up to 5 years | | |

For the latest compatibility details, please contact our sales representatives.
 For detailed dimension, please visit Infortrend website.
 Options may vary by region.





| Model | JB 360R | JB 360G | |
|---|---|--|--|
| Form factor ² | 4U LFF 19-inch rackmount | | |
| Drive bay | 60 | | |
| Controller | Dual redundant Single | | |
| Host/Expansion connectivity (per controller) | 3 x 12Gb/s Mini SAS HD ports (SFF-8644) | | |
| Controller support | LSI 12Gb/S SAS RAID card - MegaRAID SAS 9380-8e | | |
| Supported drives ¹ | 3.5" 7200RPM SAS/2.5" 10K RPM SAS, 2.5" 15K RPM SAS | | |
| Maximun drives (via expansion to additional enclosures) | 180 | | |
| Hot-swappable power supply | Two redundant 1600W | | |
| Green design | 80 PLUS power supplies delivering more than 80% energy efficiency | | |
| Avaiability | Redundant, hot-swappable hardware modules | | |
| Notification | LED status | | |
| | Standard service | 3-year limited hardware/software warranty and 8x5 phone, web and email support | |
| Service and Support | Upgrade/Extension Options ³ | Replacement part dispatch on the next business day (up to 5 years) Advanced Service: 24x7 phone, web and email support + onsite diagnostics on the next business day (up to 5 years) Premium Service: 24x7 phone, web and email support + onsite diagnostics in 4 hours (up to 5 years) Extended Standard Service up to 5 years | |





| Model | JB 360RL⁴ | JB 360GL⁴ | |
|---|---|---|--|
| Form factor ² | 4U LFF 19-inch rackmount | | |
| Drive bay | 60 | | |
| Controller | Dual redundant Single | | |
| Host/Expansion connectivity (per controller) | 3 x 12Gb/s Mini SAS HD ports (SFF-8644) | | |
| Controller support | LSI 12Gb/S SAS RAID card - MegaRAID SAS 9380-8e | | |
| Supported drives ¹ | 3.5" 7200RPM SAS/2.5" 10K RPM SAS, 2.5" 15K RPM SAS | | |
| Maximun drives (via expansion to additional enclosures) | 180 | | |
| Maintenane efficiency | HDD tray is screwless design(3.5" 7200 RPM SAS HDD only) | | |
| Hot-swappable power supply | Two redundant 1200W | | |
| Green design | 80 PLUS power supplies delivering more than 80% energy efficiency | | |
| Avaiability | Redundant, hot-swappable hardware modules | | |
| Notification | LED status | | |
| | Standard service | 3-year limited hardware/software warranty and 8x5 phone, web and email support | |
| Service and Support | Upgrade/Extension Options ³ | Replacement part dispatch on the next business day (up to 5 years) Advanced Service: 24x7 phone, web and email support + onsite diagnostics on the next business day (up to 5 years) | |
| | | Premium Service: 24x7 phone, web and email support + onsite diagnostics in 4 hours (up to 5 years) Extended Standard Service up to 5 years | |

- For the latest compatibility details, please contact our sales representatives.
 For detailed dimension, please visit Infortrend website.
 Options may vary by region.
 One drawer design with following dimension: 448mm(W) x 176mm(H) x 860mm(L) (Exclude CMA)/ 448mm(W) x 176mm(H) x 990mm(L) (Include CMA)



Asia Pacific (Taipei, Taiwan) | China (Beijing, China) | Japan (Tokyo, Japan) | Infortrend Technology, Inc. | Infortrend Technology, Ltd. | Infortrend Japan, Inc.

Americas (Sunnyvale, CA, USA) Infortrend Corporation

EMEA (Basingstoke, UK)
Infortrend Europe Ltd.



Infortrend Technology, Inc. www.infortrend.com

Tel:+886-2-2226-0126 E-mail: sales.ap@infortrend.com

Tel:+86-10-6310-6168 E-mail: sales.cn@infortrend.com

 $\begin{array}{lll} \mbox{Tel:} + 81 \hbox{-} 3 \hbox{-} 5730 \hbox{-} 6551 & \mbox{Tel:} + 1 \hbox{-} 408 \hbox{-} 988 \hbox{-} 5088 \\ \mbox{E-mail:} sales.jp@infortrend.com & \mbox{E-mail:} sales.us@infortrend.com \\ \end{array}$

Tel:+44-1256-305-220 E-mail: sales.eu@infortrend.com